



NOTES:

1. HOT-MIX RAMPING SHALL BE INSTALLED AROUND ALL MANHOLES, VALVES, AND CLEANOUTS WITHIN PAVED AREA IN ACCORDANCE WITH THESE NOTES AT THE TIME OF HOT-MIX BASE INSTALLATION.
2. MAXIMUM EXPOSURE OF CASTING PRIOR TO RAMPING SHALL NOT EXCEED 3 INCHES. THIS MAY REQUIRE MULTIPLE HEIGHT ADJUSTMENTS OF THE CASTING DURING PAVEMENT INSTALLATION.
3. MAXIMUM SLOPE OF RAMPING SHALL NOT EXCEED 5 PERCENT.
4. RAMPING MATERIAL SHALL BE MAINTAINED/REPAIRED UNTIL FINAL COURSE OF PAVEMENT IS INSTALLED.
5. RAMPING MATERIAL SHALL BE REMOVED JUST PRIOR TO FINAL PAVEMENT COURSE OVERLAY.
6. IF HOT-MIX RAMPING OCCURS ON A DELDOT MAINTAINED ROADWAY, RAMPING REQUIREMENTS MAY BE DIFFERENT THAN THOSE SHOWN ON THIS DETAIL.



SUSSEX COUNTY
ENGINEERING DEPARTMENT

APPROVED: *[Signature]*
SUSSEX COUNTY ENGINEER

HOT-MIX RAMPING
AT MANHOLE

DETAIL
S-1.13

DATE ISSUED:
12/30/2021