BUILDING CODE

ANDY WRIGHT CHIEF OF BUILDING CODE (302) 855-7860 T (302) 855-7869 F





EXCEPTIONS TO 2012 IRC

IRC 2012

- 1. R-309.2 Carports
- 2. R-311.3 Landings. There shall be a landing or floor on each side of exterior door.
- 3. R-311.7.5.1 Riser Height. Maximum riser height shall be 7 ¾"
- R-311.7.5.1 Riser Height Difference. The greatest riser height within any flight of stairs shall not exceed the smallest by more than 3/8"
- 5. R-311.7.5.2 Tread Depth. Minimum tread depth shall be 10".
- R-403.1.6 Foundation Anchorage. There shall be a minimum of two bolts per plate section with one bolt located not more than 12" from each end of the plate section.
- 7. R-313 Automatic Fire Sprinkler System An automatic residential fire sprinkler system shall be installed in townhouses and one- and two- family dwellings.

EXCEPTIONS

Carports will be excluded from inspections.

A landing is not required on the exterior of a sliding door.

Maximum riser height 8 ¼"

The first & last step, of interior stairs, may have a difference of 5/8"

Minimum tread depth 9" including winders.

No anchor bolts will be required at the end of each plate section, excluding corners.

No automatic residential fire sprinkler system will be required in townhouses and one- and two- family dwellings, under four stories.

